

## WC-ATV-10 Visual Fault Locator

### Description:

ATV-10 Visual Fault Locator can quickly identify the continuity of a fibre within a network.

### ATV-10 Visual Fault Locator



### Standard Package





## Features & Applications

### Features:

AA alkaline batteries

Pulse and CW operation

Small, portable and durable

### Specifications:

Model	ATV-10-1	ATV-10-10	ATV-10-20	ATV-10-30
Output Power	≥1mW	≥10mW	≥20mW	≥30mW
Detecting Range	About 5km	About 10Km	About 14km	About 15km
Laser Launcher Type	FP-LD			
Optical Connector	universal 2.5mm adapter (FC/SC/ST)			
Output Wavelength	650nm±20nm			
Modulation Frequency	CW / 2Hz			
Power	2*AA dry batteries			
Working Temperature	-10°C~+50°C; <90%RH			
Storage Temperature	-20°C~+70°C; <90%RH			
Dimension	L180mm×D25mm			
Weight	80g			
<b>Standard Accessories:</b>				
Visual Fault Locator with universal 2.5mm adapter (FC/SC/ST)				
<b>Optional Accessories:</b>				
Male FC to female LC adapter for LC connector, 2*AA dry batteries				
<b>Customization:</b>				
Visual Fault Locator with universal 1.25mm adapter (LC/MU)				